



OpenVox SWG20XX-4S Series Wireless Gateway

Overview

OpenVox SWG2016/32-4S is a Multi-SIM version of the SWG series wireless gateways, including SWG2016/32G/L-4S. The SWG2016/32-4S series wireless gateway provides 16/32 GSM/LTE channels, corresponding to 64/128 SIM cards. The SWG2016/32-4S series wireless gateways support multiple codecs, including G.711U, G.711A, GSM, G.722, G.726, and G.729. The SWG2016/32-4S series gateway is perfectly compatible with Asterisk, 3CX, FreePBX, FreeSWITCH sip server, and the VOS VoIP system platform. It can provide users with more diverse telecommunications access methods and helps users reduce communication costs.

The SWG2016/32-4S series gateway is built in an Intel 4-core CPU and has incredible processing capacity. The SWG2016/32-4S series gateways have a unique LCD screen design, you can clearly see the status of each channel on this screen. You can easily implement multiple functions through the button next to the display screen, such as viewing gateway system-related information, configuring network information, restarting the gateway, or restoring factory settings without logging into the WEB page.

VoIP Characters

- Support SIP/IAX2 Protocol
- DTMF Mode: RFC2833/Inband/SIP Info
- SIP V2.0 RFC3261 Compliance
- Abundant Codecs:G.711A, G.711U, G.729, G.722, G.726, GSM
- Work as both SIP Client and Server mode

Network

- IPv4, UDP/TCP, ARP, DHCP, NTP, DNS, HTTP/HTTPS, SSH
- PPTP VPN
- Ping & Traceroute
- Firewall

Management

- Friendly GUI and easy configuration
- WEB/SSH Access and Management
- Support configuration files backup and restore
- Support multiple languages
- Firmware Update by Web
- CDR
- Detailed Log
- Network and SIP capture

System Features

- SIP/IAX2/Wireless Group Settings
- Random call interval
- Call Duration Limitation
- Open API Protocol (based on Asterisk)
- Two-stage dialing
- Multiple SMS API
- SMS/USSD
- PIN Identification
- SMS Bulk Transceiver and Auto Resend
- SMS to Email
- SMS Forwarding and Quick Reply
- SMS Remotely Controlling Gateway
- Flexible Call Routings
- Schedule Reboot
- Support MMP
- Support for Custom Scripts, Dialplans
- Support OpenVox Cloud Service
- CLID Display & Hide (Need operators' support)



Specifications

SWG20XX-4S G/L Series					
Product Name	SWG2016G-4S	SWG2032G-4S	SWG2016L-4S	SWG2032L-4S	
Module Type	GSM		LTE		
Module Number	16	32	16	32	
Sim Slot Number	64	128	64	128	
Band	GSM: 850/900/1800/1900MHz		China/India LTE FDD: B1/B3/B5/B8 LTE TDD: B38/B39/B40/B41 WCDMA: B1/B8 TD-SCDMA: B34/B39 CDMA: BC0	Europe/Middle East/Africa/ Korea/Thailand LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8	Australia/New Zealand/ Taiwan/Brazil LTE FDD: B1/B2/B3/B4/B5/ B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8 GSM: B2/B3/B5/B8
Weight (without antenna)	3.575kg	4.525kg	3.655kg	4.685kg	
Power	16W	35W	16W	35W	
Dimension (without antenna)	440mm*44mm*300mm	440mm*88mm*300mm	440mm*44mm*300mm	440mm*88mm*300mm	
SIM Card	Hot-Swap				
LCD dimension	2.4"				
LCD resolution ratio	240*400				
LAN	1* 10/100M				
WAN	1* 10/100M				
USB	1(Supports USB storage)				
TF	1(Supports TF Card storage)				
Console	1				
Operation Temperature	0°C ~ 40°C				
Operation Humidity Range	10% ~ 90%				
Storage Temperature Range	-20°C ~ 70°C				

Address: Room 624, 6/F, Tsinghua Information Port, Book Building, Qingxiang Road, Longhua Street, Longhua District, Shenzhen, Guangdong, China 518109

Tel: +86-755-66630978,82535461, 82535362

Business Contact: sales@openvox.cn, Technical Support: support@openvox.cn Website: www.openvoxtech.com